

EHLR 95 Specifications

Stainless steel

Walsted Truck A/S

Flexible solutions

Type			EHLR 95
Capacity	Q Load	kg	2500
Power type	Electric (battery)		Battery
Control type	Electric power steering		Walking/standing
Tyre equipment	Number / P = Polyurethane (single or bogie)		(2 or 4x) P
Wheels	Number / type V = Vulkollan		(2x) V
Turning radius	Wa (without platform)	mm	1821
Turning radius	Wa (with platform)	mm	2265
Aisle width	AST For pallet 800x1200(without platform)mm		2198
Aisle width	AST For pallet 800x1200 (with platform) mm		2640
Speeds	Driving speed without/with load		km/h 6/5,4-(11,5/8,5**)
Gardability	Without/with load		% 10/10
Weight	Excl. battery		kg 600
Brakes	Type		Electric
Parking brake	Type		Electric
Battery	Acid, stainless steel box, 265 kg		V/Ah 24/344
	GEL, stainless steel box, 250 kg		V/Ah 24/284
	Lithium-Ion, stainless steel box, 265 kg		V/Ah 24/200
Drive motor	Drive motor power /S2 min.		KW/min. 2x1,5/60
	Pump motor power/S3		KW/%. 2,2/-
Speed control			Variable

These specifications are subject to change without notice.

** With side guards

*Without platform.

